

Safety Data Sheet

according to Regulation (EC)
No 1907/2006 (REACH) as amended

FUEL INJECTOR CLEANER

TEC-2000 LTD.

P. O. BOX 285, Hitchin, HERTS.. SG4 9WQ. U.K.

info@TEC-2000.co.uk

PH: 01462-433 660 FAX: 01462-674 468 MOB: 07831-105 386

Version Number: 17 Revision Date: 14-Jun-2022

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product Identifier TEC-2000 FUEL INJECTOR CLEANER

Substance / mixture mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against

Mixture's intended use

Clean Fuel Injectors (& Carburettors) Of Petrol Engines In Situ.

Main intended use

PC-CLN-OTH Other cleaning, care and maintenance products (excludes biocidal products)

Mixture uses advised against

The product should not be used in ways other then those referred in Section 1.

1.3 Details of the supplier of the safety data sheet

Manufacturer:

Name or trade name TEC-2000 LIMITED

Address PO Box 285, Hitchin, Hertfordshire, SG4 9WQ United Kingdom

 VAT Reg No
 GB111112414

 Phone
 +44 (0) 1462 433 660

 E-mail
 mike@tec-2000.co.uk

 Web address
 www.tec-2000.co.uk

 Competent person responsible for the safety data sheet

Name TEC-2000 LIMITED
E-mail mike@tec-2000.co.uk

1.4 Emergency telephone number

0044 (Ø) 7831 105386 (24hrs)

NHS Direct: 111

UK-National Poisons Information Service (NPIS): 0344 892 0111 (healthcare professionals only). Ireland - National Poisons Information Centre (NPIC): (01) 809 2566 (healthcare professionals only).

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

The mixture is classified as dangerous.

Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 Eye Dam. 1, H318 STOT SE 3, H335, H336 STOT RE 2, H373 Aquatic Chronic 2, H411

Full text of all classifications and hazard statements is given in the section 16

Most serious adverse physico-chemical effects

Highly flammable liquid and vapour.

Most serious adverse effects on human health and the environment

May be fatal if swallowed and enters airways. May cause respiratory irritation. May cause drowsiness or dizziness. Causes skin irritation. May cause damage to organs through prolonged or repeated exposure. Causes serious eye damage. Toxic to aquatic life with long lasting effects.





TEC-2000 Fuel Injector Cleaner

Revision Date: 14-Jun-2022

2.2 Label elements

Hazard pictograms:











Signal word:

Danger

Hazardous substances

Petroleum light aromatic C9

acetone propan-2-ol xylene

Poly(oxy-1,2-ethanediyl), .alpha.-tridecyl-.omega.-hydroxy-

Hazard statements:

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation

H318 Causes serious eye damage. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands and exposed parts of the body thoroughly after handling.

Use only outdoors or in a well-ventilated area. P271

Wear protective gloves/protective clothing/eye protection/face protection. P280

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact P305+P351+P338

lenses, if present and easy to do. Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention. P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container to according to local/by regional/according to

national/by international regulations.

Supplemental information:

EUH066 Repeated exposure may cause skin dryness or cracking.

>30% aromatic hydrocarbons, <5% non-ionic surfactants

Requirements for child-resistant fastenings and tactile warning of danger

Container must carry a tactile warning of danger. Container must be fitted with child-resistant fastening.

2.3 Other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605. Mixture does not contain any substance meet the criteria for PBT or vPvB in accordance with Annex XIII of Regulation (EC) No. 1907/2006 (REACH) as amended.

SECTION 3: Composition/information on ingredients

3.2 Mixtures

Chemical characterization

Mixture.

Mixture contains these hazardous substances and substances with the highest permissible concentration in the working environment.

Identification numbers	Substance name	Content in % weight	Classification according to Regulation (EC) No 1272/2008	Note
CAS: 64742-95-6 EC: 918-668-5 Registration number: 01-2119455851-35-XXXX	Petroleum light aromatic C9	25-60	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335, H336 Aquatic Chronic 2, H411	
ndex: 606-001-00-8 CAS: 67-64-1 EC: 200-662-2 Registration number: 01-2119471330-49-XXXX	Acetone	20-25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 EUH066	2
Index: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7 Registration number: 01-2119457558-25- XXXX	propan-2-ol	20-25	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	
Index: 601-022-00-9 CAS: 1330-20-7 EC: 215-535-7 Registration number: 01- 2119488216-32- XXXX	Xylene	10-<20	Flam. Liq. 3, H226 Asp. Tox. 1, H304 Acute Tox. 4, H312+H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 Aquatic Chronic 3, H412	1,
CAS: 24938-91-8	Poly(oxy-1,2-ethanediyl), .alphatridecylomegahydroxy-	3-<5	Acute Tox. 4, H302 Eye Dam. 1, H318	

Notes

- Note C: Some organic substances may be marketed either in a specific isomeric form or as a mixture of several isomers. In this case the supplier must state on the label whether the substance is a specific isomer or a mixture of isomers.
- 2 Substance with a Union workplace exposure limit.

Full text of all classifications and hazard statements is given in the section 16.

SECTION 4: First aid measures

4.1 Description of first aid measures

Do not perform artificial respiration without self-protection (e.g. a mask). Take care of your own safety. If any health problems are manifested or if in doubt, inform a doctor and show him information from this safety data sheet. If unconscious, put the person in the stabilized (recovery) position on his side with his head slightly bent backwards and make sure that airways are free; never induce vomiting. If the person vomits by himself, make sure that the vomit is not inhaled. In life threatening conditions first of all provide resuscitation of the affected person and ensure medical assistance. Respiratory arrest - provide artificial respiration immediately. Cardiac arrest - provide indirect cardiac massage immediately.

If inhaled

Take care of your own safety, do not let the affected person walk! Terminate the exposure immediately; move the affected person to fresh air. Beware of the contaminated clothes. Depending on the situation, call the medical rescue service and ensure medical treatment considering the frequent need of further observation for at least 24 hours.

If on skin

Remove contaminated clothes. Wash the affected area with plenty of water, lukewarm if possible. Soap, soap solution or shampoo should be used if there is no skin injury. Provide medical treatment if skin irritation persists. Rinse skin with water or shower.

If in eyes

Rinse eyes immediately with a flow of running water, open the eyelids (also using force if needed); remove contact lenses immediately if worn by the affected person. No neutralization should be performed in any case! Rinsing should be continued for 10-30 minutes from the inner to the outer eye corner to make sure that the other eye is not involved. Depending on the situation, call medical rescue service or ensure medical treatment as promptly as possible. Everyone must be referred for treatment even if affected only a little.

If swallowed

If the affected person vomits, make sure to prevent inhalation of the vomit (as there is a danger of lung damage after inhalation of these liquids in the airways also in infinitesimal amount). Ensure medical treatment considering the frequent need of further observation for at least 24 hours. Bring an original container with the label and the Safety Data Sheet of the given substance as appropriate.

4.2 Most important symptoms and effects, both acute and delayed

If inhaled

Inhaling vapours can cause corrosion of the breathing system. Cough, headache. May cause respiratory irritation. May cause drowsiness or dizziness.

If on skin

Causes skin irritation.

If in eyes

Causes serious eye damage.

Version Number: 17 **TEC-2000 Fuel Injector Cleaner** Revision Date: 14-Jun-2022

If swallowed

Corrosion of the digestion system can occur.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting Measures

5.1 Extinguishing media

Suitable extinguishing media

Alcohol-resistant foam, carbon dioxide, powder, water spray jet, water mist.

Unsuitable extinguishing media

Water - full jet.

5.2 Special hazards arising from the substance or mixture

In the event of fire, carbon monoxide, carbon dioxide and other toxic gases may arise. Inhalation of hazardous degradation (pyrolysis) products may cause serious health damage.

5.3 Advice for firefighters

Self-Contained Breathing Apparatus (SCBA) with a chemical protection suit only where personal (close) contact is likely. Use a self-contained breathing apparatus and full-body protective clothing. Closed containers with the product near the fire should be cooled with water. Do not allow run-off of contaminated fire extinguishing material to enter drains or surface and ground water.

SECTION 6: Accidental Release Measures

6.1 Personal precautions, protective equipment and emergency procedures

Provide sufficient ventilation. Highly flammable liquid and vapour. Remove all ignition sources. Use personal protective equipment for work. Follow the instructions in the Sections 7 and 8. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes.

6.2 Environmental precautions:

Do not allow to enter drains. Prevent contamination of the soil and entering surface or ground water.

6.3 Methods and material for containment and cleaning up

Spilled product should be covered with suitable (non-flammable) absorbing material (sand, diatomaceous earth, earth and other suitable absorption materials); to be contained in well closed containers and removed as per the Section 13. In the event of leakage of the substantial amount of the product, inform fire brigade and other competent bodies. After removal of the product, wash the contaminated site with plenty of water. Do not use solvents.

6.4 Reference to other sections

See the Section 7, 8 and 13.

SECTION 7: Handling and Storage

7.1 Precautions for safe handling:

Prevent formation of gases and vapours in flammable or explosive concentrations and concentrations exceeding the occupational exposure limits. The product should be used only in the areas where it is not in contact with open fire and other ignition sources. Use non-sparking tools. Use of antistatic clothes and footwear is recommended. Do not inhale mist/vapours/spray. Prevent contact with skin and eyes. No smoking. Wash hands and exposed parts of the body thoroughly after handling. Use only outdoors or in a well-ventilated area. Use personal protective equipment as per Section 8. Observe valid legal regulations on safety and health protection. Ground and bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Take action to prevent static discharges. Avoid release to the environment.

7.2 Conditions for safe storage, including any incompatibilities:

Store in tightly closed containers in cold, dry and well ventilated areas designated for this purpose. Do not expose to sunlight. Store locked up. Keep container tightly closed. Keep cool.

The specific requirements or rules relating to the substance/mixture

Solvent vapours are heavier than air and accumulate especially near the floor where they may form an explosive mixture with the air.

7.3 Specific end use(s):

The mixture contains substances for which occupational exposure limits are set.

SECTION 8: Exposure Controls/Personal Protection

8.1 Control parameters

The mixture contains substances for which occupational exposure limits are set.

European Union

Commission Directive 2000/39/EC

Substance name (component)	Туре	Value	Note
acetone (CAS: 67-64-1)	OEL 8 hours	1210 mg/m³	
	OEL 8 hours	500 ppm	
	OEL 8 hours	221 mg/m³	
xylene (CAS: 1330-20-7)	OEL 8 hours	50 ppm	Skin
Xylefie (CAS. 1550-20-7)	OEL 15 minutes	442 mg/m³	SKIT
	OEL 15 minutes	100 ppm	

TEC-2000 Fuel Injector Cleaner Revision Date: 14-Jun-2022

8.2 Exposure controls

Follow the usual measures intended for health protection at work and especially for good ventilation. This can be achieved only by local suction or efficient general ventilation. If exposure limits cannot be observed in this mode, suitable protection of airways must be used. Do not eat, drink and smoke during work. Wash your hands thoroughly with water and soap after work and before breaks for a meal and rest.

Eye/face protection

Protective goggles or face shield (based on the nature of the work performed).

Skin protection

Hand protection: Protective gloves resistant to the product. When choosing appropriate thickness, material and permeability of the gloves, observe recommendations of their particular manufacturer. Observe other recommendations of the manufacturer. Other protection: protective workwear. Contaminated skin should be washed thoroughly.

Respiratory protection

Mask with a filter in a poorly ventilated environment.

Thermal hazard

Data not available.

Environmental exposure controls

Observe usual measures for protection of the environment, see Section 6.2. Collect spillage.

SECTION 9: Physical and Chemical Properties

9.1 Information on basic physical and chemical properties

Physical state liquid Colour red

data not available Odour Melting point/freezing point data not available

Boiling point or initial boiling point and boiling range 56 °C

Flammability data not available

Lower and upper explosion limit

bottom 0,8 % 13,3 % upper 0°C Flash point

Auto-ignition temperature data not available Decomposition temperature data not available рΗ non-soluble (in water) Kinematic viscosity data not available Solubility in water data not available Partition coefficient n-octanol/water (log value) data not available Vapour pressure data not available Density and/or relative density data not available Relative vapour density data not available Particle characteristics data not available

9.2 Other information

not available

SECTION 10: Stability and Reactivity

10.1 Reactivity:

not available

10.2 Chemical stability

The product is stable under normal conditions.

10.3 Possibility of hazardous reactions:

Unknown.

10.4 Conditions to avoid:

The product is stable and no degradation occurs under normal use. Protect against flames, sparks, overheating and against frost.

10.5 Incompatible materials:

Protect against strong acids, bases and oxidizing agents.

10.6 Hazardous decomposition products:

Not developed under normal uses. Dangerous outcomes such as carbon monoxide and carbon dioxide are formed at high temperature and in fire.

SECTION 11: Toxicological Information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Inhalation of solvent vapors above values exceeding exposure limits for working environment may result in acute inhalation poisoning, depending on the level of concentration and exposure time. No toxicological data is available for the mixture.

Acute toxicity

Based on available data the classification criteria are not met.

TEC-2000 Fuel Injector Cleaner Version Number: 17 Revision Date: 14-Jun-2022

acetone

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5800 mg/kg		Rat	
Derma	LD ₅₀	20000 mg/kg		Rabbit	
propan-2-ol					

Route of exposure	Parameter	Value	Exposure time	Species	Sex
Oral	LD ₅₀	5840 mg/kg		Rat propan-2-ol	
Dermal	LD ₅₀	12800 mg/kg		Rabbit	
Inhalation	LD ₅₀	30 mg/l	4 hour	Rat	

xylene

Ro	oute of exposure	Parameter	Value	Exposure time	Species	Sex
Ora	al	LD_{50}	4300 mg/kg		Rat	
De	ermal	LD ₅₀	2000 mg/kg		Rabbit	

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye damage.

Respiratory or skin sensitisation

Based on available data the classification criteria are not met.

Germ cell mutagenicity

Based on available data the classification criteria are not met.

Carcinogenicity

Based on available data the classification criteria are not met.

Reproductive toxicity

Based on available data the classification criteria are not met.

Toxicity for specific target organ - single exposure

May cause respiratory irritation. May cause drowsiness or dizziness.

Toxicity for specific target organ - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard

May be fatal if swallowed and enters airways.

11.2 Information on other hazards

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

SECTION 12: Ecological information

12.1 Toxicity

Acute toxicity

Toxic to aquatic life with long lasting effects.

Petroleum Light aromatic C9

Parameter	Value	Exposure time	Species	Environment		
EC ₅₀	3.2 mg/l	48 hour	Daphnia			
propan-2-ol						
Parameter	Value	Exposure time	Species	Environment		
LC ₅₀	9640 mg	96 hour	Fishes			
LC ₅₀	>10000 mg	24 hour	Daphnia			

Chronic toxicity

propan-2-ol

Parameter	Value	Exposure time	Species	Environment
NOEC	1050 mg/l		Microorganisms	

12.2 Persistence and degradability:

Biodegradability

Petroloum light are

retioleum light aromatic C9						
Parameter	Value	Exposure time	Environment	Result		
	>60 %	28 dav		Biodegradable		

The mixture is biodegradable.

12.3 Bioaccumulative potential:

Data not available.

12.4 Mobility in soil:

Data not available

Version Number: 17 **TEC-2000 Fuel Injector Cleaner** Revision Date: 14-Jun-2022

12.5 Results of PBT and vPvB assessment

Product does not contain any substance meeting the criteria for PBT or vPvB in accordance with the Annex XIII of Regulation (EC) No 1907/2006 (REACH) as amended.

12.6 Endocrine disrupting properties

The mixture does not contain substances with endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605.

12.7 Other adverse effects:

Data not available.

SECTION 13: Disposal Considerations

13.1 Waste treatment methods

Hazard of environmental contamination; dispose of the waste in accordance with the local and/or national regulations. Proceed in accordance with valid regulations on waste disposal. Any unused product and contaminated packaging should be put in labelled containers for waste collection and submitted for disposal to a person authorised for waste removal (a specialized company) that is entitled for such activity. Do not empty unused product in drainage systems. The product must not be disposed of with municipal waste. Empty containers may be used at waste incinerators to produce energy or deposited in a dump with appropriate classification. Perfectly cleaned containers can be submitted for recycling.

Waste management legislation

Directive 2008/98/EC of the European Parliament and of the Council of 19 November 2008 on waste, as amended. Decision 2000/532/EC establishing a list of wastes, as amended.

SECTION 14: Transport Information

14.1 UN Number or ID number

UN 1268

14.2 UN proper shipping name

PETROLEUM DISTILLATES, N.O.S. (Petroleum Light aromatic C9)

14.3 Transport hazard class(es)

3 Flammable liquids

14.4 Packing group

III - substances presenting low danger

14.5 Environmental hazards:

not relevant

14.6 Special precautions for user

not available

14.7 Maritime transport in bulk according to IMO instruments

not relevant

Additional information

Hazard identification No.

UN number

Classification code

1268

F1

Safety signs 3+hazardous for the environment



Marine transport - IMDG

EmS (emergency plan) F-E, S-E MFAG 310

SECTION 15: Regulatory Information.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Regulation (EC) No. 1907/2006 of the European Parliament and of the Council of 18th December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (REACH), establishing the European Chemicals Agency, amending Directive 1999/45/EC and repealing Council Regulation (EEC) No. 793/93 and Commission Regulation (EC) No. 1488/94 as well as Council Directive 76/769/EEC and Commission Directives 91/155/EEC, 93/67/EEC, 93/105/EC and 2000/21/EC, as amended. Regulation (EC) No. 1272/2008 of the European Parliament and of the Council of 16th December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No. 1907/2006, as amended. REGULATION (EC) No 648/2004 OF THE EUROPEAN PARLIAMENTAND OF THE COUNCIL of 31 March 2004 on detergents, as amended. Product contains reportable explosives precursors: Reporting of suspicious transactions, disappearances and thefts according to Regulation (EU) 2019/1148, Article 9.

15.2 Chemical safety assessment:

not available

Version Number: 17 **TEC-2000** Fuel Injector Cleaner Revision Date: 14-Jun-2022

SECTION 16: Other Information.

A list of standard risk phrases used in the safety data sheet

H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H335 May cause respiratory irritation.
 H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

H411 Toxic to aquatic life with long lasting effects.
H412 Harmful to aquatic life with long lasting effects.
H312+H332 Harmful in contact with skin or if inhaled.

Guidelines for safe handling used in the safety data sheet

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P271 Use only outdoors or in a well-ventilated area.

P264 Wash hands and exposed parts of the body thoroughly after handling.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue

rınsıng.

P362+P364 Take off contaminated clothing and wash it before reuse. P332+P313 If skin irritation occurs: Get medical advice/attention.

P405 Store locked up.

P501 Dispose of contents/container to according to local/by regional/according to national/by international regulations.

A list of additional standard phrases used in the safety data sheet

EUH066 Repeated exposure may cause skin dryness or cracking.

Other important information about human health protection

The product must not be - unless specifically approved by the manufacturer/importer - used for purposes other than as per the Section 1.

The user is responsible for adherence to all related health protection regulations

Key to abbreviations and acronyms used in the safety data sheet

ADR European agreement concerning the international carriage of dangerous goods by road

BCF Bioconcentration Factor
CAS Chemical Abstracts Service

CLP Regulation (EC) No 1272/2008 on classification, labelling and packaging of substance and mixtures

EC₅₀ Concentration of a substance when it is affected 50% of the population EINECS European Inventory of Existing Commercial Chemical Substances

EmS Emergency plan

ES Identification code for each substance listed in EINECS

EU European Union

EuPCS European Product Categorisation System IATA International Air Transport Association

IBC International Code For The Construction And Equipment of Ships Carrying Dangerous Chemicals

ICAO International Civil Aviation Organization IMDG International Maritime Dangerous Goods

INCI International Nomenclature of Cosmetic Ingredients
ISO International Organization for Standardization
IUPAC International Union of Pure and Applied Chemistry

LC₅₀ Lethal concentration of a substance in which it can be expected death of 50% of the population

LD₅₀ Lethal dose of a substance in which it can be expected death of 50% of the population

log Kow Octanol-water partition coefficient

MARPOL International Convention for the Prevention of Pollution from Ships

NOEC No observed effect concentration
OEL Occupational Exposure Limits
PBT Persistent, Bioaccumulative and Toxic

ppm Parts per million

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals

RID Agreement on the transport of dangerous goods by rail

TEC-2000 Fuel Injector Cleaner

Revision Date: 14-Jun-2022

UN Four-figure identification number of the substance or article taken from the UN Model Regulations UVCB Substances of unknown or variable composition, complex reaction products or biological materials

VOC Volatile organic compounds

vPvB Very Persistent and very Bioaccumulative

Skin irritation

Acute Tox. Acute toxicity

Aquatic Chronic Hazardous to the aquatic environment (chronic)

Asp. Tox. Aspiration hazard
Eye Dam. Serious eye damage
Eye Irrit. Eye irritation
Flam. Liq. Flammable liquid

STOT RE Specific target organ toxicity - repeated exposure STOT SE Specific target organ toxicity - single exposure

Training guidelines

Version Number: 17

Inform the personnel about the recommended ways of use, mandatory protective equipment, first aid and prohibited ways of handling the product.

Recommended restrictions of use

not available

Skin Irrit.

Information about data sources used to compile the Safety Data Sheet

REGULATION (EC) No. 1907/2006 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL (REACH) as amended. REGULATION (EC) No. 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL as amended. Data

from the manufacturer of the substance / mixture, if available - information from registration dossiers.

The changes (which information has been added, deleted or modified)

The version 2.0 replaces the SDS version from 09.08.2021. Change of product composition.

More information

Classification procedure - calculation method.

Statement

The safety data sheet provides information aimed at ensuring safety and health protection at work and environmental protection. The provided information corresponds to the current status of knowledge and experience and complies with valid legal regulations. The information should not be understood as guaranteeing the suitability and usability of the product for a particular application.